UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/729,443	12/04/2000	Steven T. Jaffe	36928/NJP/B600	6265

23363 7590 09/15/2005	EXAMINER
CHRISTIE, PARKER & HALE, LLP	TORRES, JUAN A

	ART UNIT	PAPER NUMBER
CHRISTIE, PARKER & HALE, LLP PO BOX 7068 PASADENA, CA 91109-7068	2631	

DATE MAILED: 09/15/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

PTO 90C (Rev 10/03)

	Application No.	Applicant(s)
Office Action Summary	09/729,443	JAFFE ET AL.
	Examiner	Art Unit	
	Juan A. Torres	2631	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on *26 August 2005*.

2a) ☐ This action is **FINAL**.   2b) ☒ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) *1-3,5-16,18-22,24-28,30-42,44-48,50-54 and 56-61* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) *1-3,5-16,18-22,24-28,30-42,44-48,50-54 and 56-61* is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☒ The drawing(s) filed on *22 March 2005* is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☐ All   b) ☐ Some * c) ☐ None of:

      1. ☐ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____.

5) ☐ Notice of Informal Patent Application (PTO-152)

6) ☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 9, 13-14, 38-39 and 46 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the enablement requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to enable one skilled in the art to which it pertains, or with which it is most nearly connected, to make and/or use the invention. The disclosure doesn't teach the use of a third signal where the Viterbi decoding of the multiplied third signal is not based on the received third signal.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(a) the invention was known or used by others in this country, or patented or described in a printed publication in this or a foreign country, before the invention thereof by the applicant for a patent.

Claims 1-3, 5-8, 10-11, 15-16, 18-19, 21-22, 24-25, 27-28, 30-31, 33-36, 40-42, 44-45, 47-48, 50-51 and 53-54, 56-59 are rejected under 35 U.S.C. 102(a) as being anticipated by Langlais et al. ("Synchronization in the carrier recovery of a satellite link using turbo-codes with the help of tentative decisions", IEE Colloquium on Turbo Codes in Digital Broadcasting - Could It Double Capacity? 22 Nov. 1999 pages: 5/1 - 5/7).

As per claim 1 Langlais et al. teach a method of processing signals, comprising receiving first and second signals each being modulated on a carrier signal, the first signal preceding the second signal in time (figure 2 page 5/1 section II.A); multiplying each of the first and second signals with a reference signal having a reference frequency (figure 2 multiplier after y(k) page 5/1 section II.A); Viterbi decoding the multiplied first signal based on the multiplied first and multiplied second signals (figure 2 phase detector page 5/1 section II.A, the Viterbi decoding is done in DEC1 and feed to the mapper); comparing the Viterbi decoded first signal to the multiplied first signal (figure 2 phase detector page 5/1 section II.A); adjusting the reference frequency as a function of the comparison (figure 2 output of loop filter page 5/1 section II.A); and turbo decoding a signal with adjusted frequency (figure 2 modulo of turbo-decoder pages 5/1-5/2 section II.A), where the Viterbi decoding is independent of the turbo decoding (page 5/1 last paragraph "A tentative decision is extracted from the turbo decoder during the decoding process, and not after the complete decoding. Although the reliability of the decision improves along with the iterative process, we cannot use a decision with an excessive delay in order to guarantee the stability of the phase-locked loop (PLL); thus since the delay introduced by the interleaver is too long, the extraction of the TD is performed before the first interleaver", so the Viterbi decoder is independent of the turbo decoding because it is perform before the turbo decoding and doesn't use the output of the turbo decoder, in fact the first Viterbi decoder will only take into account the first encoder, and it is performed before the deinterleaver, so the turbo decoding process is not taken into account). The specification doesn't disclose what "independent" means,

so the Examiner has used what he thinks is the best definition that applies to this case.

The Viterbi decoder is independent of the turbo decoding because it is perform before

the turbo decoding and doesn't use the output of the turbo decoder, in fact the Viterbi

decoder is performed before the deinterleaver and only take into account the first

encoder without considering the interleraving/deinterleaving process inherently in the

turbo coding/decoding, and it, that means that the turbo decoding process is not taken

into account, so it is independent of the turbo decoding.

As per claim 2 Langlais et al. teach a method where the first and second signals

each comprises turbo-encoded data (figure 2 page 5/1 section II.A first paragraph).

As per claim 3 Langlais et al. teach that the multiplied first and multiplied second

signals each comprises a baseband signal (figure 2 output of mapper page 5/1 section

II.A first paragraph and reference [7]).

As per claim 5 Langlais et al. teach that the comparison of the Viterbi decoded

first signal with the multiplied first signal comprises detecting a phase difference

between the Viterbi decoded first signal and the multiplied first signal (figure 2 and page

5/1 section II.A).

As per claim 6 Langlais et al. teach that the adjustment of the reference

frequency comprises tuning a voltage controlled oscillator as a function of the phase

difference between the Viterbi decoded first signal and the multiplied first signal (figure 2

and page 5/1 section II.A, the VCO in inherited in the PLL see figure 3).

As per claim 7 Langlais et al. teach that the adjustment of the reference frequency comprises adjusting the reference frequency to be substantially equal to a frequency of the carrier signal (figure 2 and page 5/2 section III.A).

As per claim 8 Langlais et al. teach that the first and second received signals each comprises a symbol representing a constellation point, and where the Viterbi decoded of the multiplied first signal comprises quantizing the multiplied first signal to its nearest constellation point as a function of the multiplied first and multiplied second signals (figure 2 and page 5/1 section II.A).

As per claim 10 Langlais et al. teach that the transmitting signals including the first and second signals, where the receiving of the first and second signals comprises receiving the transmitted signals (figure 2 and page 5/1 section II.A).

As per claim 11 Langlais et al. teach that the transmission of the signals comprises turbo encoding the signals before transmission (figure 2 and page 5/1 section II.A inherit to the turbo decoder will be a turbo encoder).

As per claim 15 Langlais et al. teach a receiver, comprising: an oscillator having a reference signal output with a tunable reference frequency (figure 2 and page 5/1 section II.A the VCO in inherited in the PLL see figure 3); a multiplier to multiply a first signal with the reference signal, and to multiply a second signal, succeeding the first signal in time, with the reference signal, the first and second signals each being modulated on a carrier frequency (figure 2 multiplier after y(k) page 5/1 section II.A); a Viterbi decoder to adjust the multiplied first signal based on the multiplied first and multiplied second signals (figure 2 block in dot lines label module of turbo-decoder page

5/1 section II.A the Viterbi decoding is done in DEC1 and feed to the mapper); a

detector to compare the adjusted first signal with the multiplied first signal, the detector

being adapted to tune the reference frequency as a function of the comparison (figure 2

phase detector page 5/1 section II.A); and a turbo decoder to turbo decode a signal with

adjusted reference frequency (figure 2 modulo of turbo-decoder pages 5/1-5/2 section

II.A), where the adjusting of the multiplied first signal by the Viterbi decoder is

independent of the turbo decoding of the signal with adjusted reference frequency (page

5/1 last paragraph "A tentative decision is extracted from the turbo decoder during the

decoding process, and not after the complete decoding. Although the reliability of the

decision improves along with the iterative process, we cannot use a decision with an

excessive delay in order to guarantee the stability of the phase-locked loop (PLL); thus

since the delay introduced by the interleaver is too long, the extraction of the TD is

performed before the first interleaver", so the Viterbi decoder is independent of the turbo

decoding because it is perform before the turbo decoding and doesn't use the output of

the turbo decoder, in fact the first Viterbi decoder will only take into account the first

encoder, and it is performed before the deinterleaver, so the turbo decoding process is

not taken into account). The specification doesn't disclose what "independent" means,

so the Examiner has used what he thinks is the best definition that applies to this case.

The Viterbi decoder is independent of the turbo decoding because it is perform before

the turbo decoding and doesn't use the output of the turbo decoder, in fact the Viterbi

decoder is performed before the deinterleaver and only take into account the first

encoder without considering the interleraving/deinterleaving process inherently in the

turbo coding/decoding, and it, that means that the turbo decoding process is not taken into account, so it is independent of the turbo decoding.

As per claim 16, 22 and 28 Langlais et al. teach that the oscillator comprises a voltage controlled oscillator (figure 2 and page 5/1 section II.A the VCO in inherited in the PLL see figure 3).

As per claim 18, 24 and 30 Langlais et al. teach that the in the Turbo4, the trellis length of DEC1 is equal to 29 bits which limits the number of accessible decoded symbols to 29 for a 1/2 rate encoder. Therefore, the possible values that delay Tr can take a: 0 α Tr α 28Ts where Ts is the symbol duration and Tr=dTs In the case of zero ·delay tentative decision, the extraction is performed at the input of the trellis. The decision results from the selection of the trellis path just after the corresponding bits have entered the DEC1 decoding trellis, this case does not consider future values of the signal only past values (page 5/2 first paragraphs).

As per claim 19, 25 and 31 Langlais et al. teach that the detector comprises a phase detector to compare a phase of the adjusted first signal with a phase of the multiplied first signal, the phase detector being adapted to tune the reference frequency as a function of a difference in phases (figure 2 phase detector page 5/1 section II.A).

As per claim 21 Langlais et al. teach a receiver, comprising an oscillator having a tuning input (figure 2 and page 5/1 section II.A the VCO in inherited in the PLL see figure 3); a multiplier having a first input to receive a signal, and a second input coupled to the oscillator, the signal comprising a first signal and a second signal succeeding the first signal in time, the first and second signals each being modulated on a carrier

frequency (figure 2 multiplier after y(k) page 5/1 section II.A); a Viterbi decoder having

an input coupled to the multiplier, and an output (figure 2 block in dot lines label module

of turbo-decoder page 5/1 section II.A the Viterbi decoding is done in DEC1 and feed to

the mapper); a detector having a first input coupled to the Viterbi decoder input, a

second input coupled to the Viterbi decoder output, and an output coupled to the tuning

input of the oscillator (figure 2 phase detector page 5/1 section II.A); and a turbo

decoder coupled to the Viterbi decoder output (figure 2 modulo of turbo-decoder pages

5/1-5/2 section II.A), where the Viterbi decoder decodes a signal input to the Viterbi

decoder independently from the turbo decoder (figure 2 modulo of turbo-decoder pages

5/1-5/2 section II.A), where the adjusting of the multiplied first signal by the Viterbi

decoder is independent of the turbo decoding of the signal with adjusted reference

frequency (page 5/1 last paragraph "A tentative decision is extracted from the turbo

decoder during the decoding process, and not after the complete decoding. Although

the reliability of the decision improves along with the iterative process, we cannot use a

decision with an excessive delay in order to guarantee the stability of the phase-locked

loop (PLL); thus since the delay introduced by the interleaver is too long, the extraction

of the TD is performed before the first interleaver", so the Viterbi decoder is independent

of the turbo decoding because it is perform before the turbo decoding and doesn't use

the output of the turbo decoder, in fact the first Viterbi decoder will only take into

account the first encoder, and it is performed before the deinterleaver, so the turbo

decoding process is not taken into account). The specification doesn't disclose what

"independent" means, so the Examiner has used what he thinks is the best definition

that applies to this case. The Viterbi decoder is independent of the turbo decoding

because it is perform before the turbo decoding and doesn't use the output of the turbo

decoder, in fact the Viterbi decoder is performed before the deinterleaver and only take

into account the first encoder without considering the interleraving/deinterleaving

process inherently in the turbo coding/decoding, and it, that means that the turbo

decoding process is not taken into account, so it is independent of the turbo decoding.

As per claim 27 Langlais et al. teach a receiver, comprising oscillator means for

generating a reference signal having a tunable reference frequency (figure 2, figure 3

and page 5/1 section II.A the VCO in inherited in the PLL); multiplier means for

multiplying a first signal with the reference signal, and multiplying a second signal,

succeeding the first signal in time, with the reference signal, the first and second signals

each being modulated on a carrier frequency (figure 2 multiplier after y(k) page 5/1

section II.A); Viterbi decoder means for adjusting the multiplied first signal based on the

multiplied first and multiplied second signals (figure 2 block in dot lines label module of

turbo-decoder page 5/1 section II.A the Viterbi decoding is done in DEC1 and feed to

the mapper); detector means for comparing the adjusted first signal with the multiplied

first signal, the detector means comprises tuning means for tuning the reference

frequency as a function of the comparison (figure 2 phase detector page 5/1 section

II.A); and turbo decoder means for turbo decoding a signal having the tuned reference

frequency (figure 2 modulo of turbo-decoder pages 5/1-5/2 section II.A), where the

adjusting of the multiplied first signal by the Viterbi decoding means is independent of

the turbo decoding of the signal having the tuned reference frequency (page 5/1 last

paragraph "A tentative decision is extracted from the turbo decoder during the decoding process, and not after the complete decoding. Although the reliability of the decision improves along with the iterative process, we cannot use a decision with an excessive delay in order to guarantee the stability of the phase-locked loop (PLL); thus since the delay introduced by the interleaver is too long, the extraction of the TD is performed before the first interleaver", so the Viterbi decoder is independent of the turbo decoding because it is perform before the turbo decoding and doesn't use the output of the turbo decoder, in fact the first Viterbi decoder will only take into account the first encoder, and it is performed before the deinterleaver, so the turbo decoding process is not taken into account). The specification doesn't disclose what "independent" means, so the Examiner has used what he thinks is the best definition that applies to this case. The Viterbi decoder is independent of the turbo decoding because it is perform before the turbo decoding and doesn't use the output of the turbo decoder, in fact the Viterbi decoder is performed before the deinterleaver and only take into account the first encoder without considering the interleraving/deinterleaving process inherently in the turbo coding/decoding, and it, that means that the turbo decoding process is not taken into account, so it is independent of the turbo decoding.

As per claim 33 Langlais et al. teach a method of processing signals having a first and second symbol each representing a constellation point, the first symbol preceding the second symbol in time, the method comprising Viterbi decoding the first symbol to its nearest constellation point as a function of the first and second signals (figure 2 d(k) output of the Viterbi decoder page 5/1 section II.A the Viterbi decoding is done in DEC1

and feed to the mapper); comparing the first symbol to the Viterbi decoded first symbol

(figure 2 phase detector page 5/1 section II.A); and adjusting a reference frequency as a

function of the comparison (figure 2 input to the multiplier page 5/1 section III.A); and

turbo decoding a signal with adjusted frequency (figure 2 modulo of turbo-decoder

pages 5/1-5/2 section II.A), where the Viterbi decoding is independent of the turbo

decoding (page 5/1 last paragraph "A tentative decision is extracted from the turbo

decoder during the decoding process, and not after the complete decoding. Although

the reliability of the decision improves along with the iterative process, we cannot use a

decision with an excessive delay in order to guarantee the stability of the phase-locked

loop (PLL); thus since the delay introduced by the interleaver is too long, the extraction

of the TD is performed before the first interleaver", so the Viterbi decoder is independent

of the turbo decoding because it is perform before the turbo decoding and doesn't use

the output of the turbo decoder, in fact the first Viterbi decoder will only take into

account the first encoder, and it is performed before the deinterleaver, so the turbo

decoding process is not taken into account). The specification doesn't disclose what

"independent" means, so the Examiner has used what he thinks is the best definition

that applies to this case. The Viterbi decoder is independent of the turbo decoding

because it is perform before the turbo decoding and doesn't use the output of the turbo

decoder, in fact the Viterbi decoder is performed before the deinterleaver and only take

into account the first encoder without considering the interleraving/deinterleaving

process inherently in the turbo coding/decoding, and it, that means that the turbo

decoding process is not taken into account, so it is independent of the turbo decoding.

As per claim 34 Langlais et al. teach a method of receiving the first and second symbols before the first symbol is Viterbi decoded (figure 2 input to the multiplier page 5/1 section III.A).

As per claim 35 Langlais et al. teach a method of transmitting the signals including the first and second symbols, where the receiving of the first and second symbols comprises receiving the transmitted signals (figure 2 input to the multiplier page 5/1 section III.A).

As per claim 36 Langlais et al. teach that the transmission of the signals comprises turbo encoding the first and second symbols before transmission (figure 2 page 5/1 section II.A first paragraph).

As per claim 40 Langlais et al. teach that the received first and second symbols are each modulated on a carrier frequency, the method further comprising multiplying each of the first and second symbols with a reference signal having the reference frequency (figure 2 multiplier page 5/1 section II.A first paragraph).

As per claim 41 Langlais et al. teach that the multiplication of the first and second modulated symbols each comprises recovering the respective symbol by removing the respective carrier frequency (figure 2 inherit to the multiplier page 5/1 section II.A first paragraph).

As per claim 42 Langlais et al. teach that the first and second symbols each comprises turbo encoded data (figure 2 page 5/1 section II.A first paragraph).

As per claim 44 Langlais et al. teach that the comparison of the first symbol with the quantized first symbol comprises detecting a phase difference between the first

symbol and the Viterbi decoded first symbol (figure 2 phase detector page 5/1 section
II.A first paragraph).

As per claim 45 Langlais et al. teach that the adjustment of the reference
frequency comprises tuning a voltage controlled oscillator as a function of the phase
difference between the first symbol and the Viterbi decoded first symbol (figure 2, figure
3 and page 5/1 section II.A the VCO in inherited in the PLL).

As per claim 47 Langlais et al. teach a receiver to receive a signal including first and
second symbols each representing a constellation point, the first symbol preceding the
second symbol in time, the receiver comprising a Viterbi decoder to quantize the first
symbol as a function of the first and second symbols (figure 2 turbo-decoder block page
5/1 section II.A the Viterbi decoding is done in DEC1 and feed to the mapper); a
detector to compare the first symbol to the quantized first symbol (figure 2 phase
detector page 5/1 section II.A); an oscillator having a tunable output as a function of the
comparison (figure 2, figure 3 and page 5/1 section II.A the VCO in inherited in the
PLL); a turbo decoder for turbo decoding an output of the Viterbi decoder (figure 2
modulo of turbo-decoder pages 5/1-5/2 section II.A), where the quantizing of the first
symbol by the Viterbi decoder is independent of the turbo decoding of the output of the
Viterbi decoder (page 5/1 last paragraph "A tentative decision is extracted from the
turbo decoder during the decoding process, and not after the complete decoding.
Although the reliability of the decision improves along with the iterative process, we
cannot use a decision with an excessive delay in order to guarantee the stability of the
phase-locked loop (PLL); thus since the delay introduced by the interleaver is too long,

the extraction of the TD is performed before the first interleaver", so the Viterbi decoder

is independent of the turbo decoding because it is perform before the turbo decoding

and doesn't use the output of the turbo decoder, in fact the first Viterbi decoder will only

take into account the first encoder, and it is performed before the deinterleaver, so the

turbo decoding process is not taken into account). The specification doesn't disclose

what "independent" means, so the Examiner has used what he thinks is the best

definition that applies to this case. The Viterbi decoder is independent of the turbo

decoding because it is perform before the turbo decoding and doesn't use the output of

the turbo decoder, in fact the Viterbi decoder is performed before the deinterleaver and

only take into account the first encoder without considering the

interleraving/deinterleaving process inherently in the turbo coding/decoding, and it, that

means that the turbo decoding process is not taken into account, so it is independent of

the turbo decoding.

As per claim 48 Langlais et al. teach that the first and second symbols are each

modulated on a carrier frequency, the receiver further comprising a multiplier to multiply

each of the first and second symbols with the oscillator output to recover its respective

symbol by removing its respective carrier frequency (figure 2, figure 3 and page 5/1

section II.A the VCO in inherited in the PLL).

As per claim 50 Langlais et al. teach that the detector comprises a phase

detector to detect a phase difference between the first symbol and the quantized first

symbol (figure 2 phase detector page 5/1 section II.A).

As per claim 51 Langlais et al. teach that the oscillator comprises a voltage

controlled oscillator (figure 2, figure 3 and page 5/1 section II.A the VCO in inherited in

the PLL).

As per claim 53 Langlais et al. teach a communication system, comprising: a transmitter

to transmit a signal including first and second symbols each representing a constellation

point, the first symbol preceding the second symbol in time (page 5/1 section I and

inherited in figure 2 and section II); and a receiver including a Viterbi decoder to

quantize the first symbol as a function of the first and second symbols (figure 2 turbo-

decoder block page 5/1 section II.A the Viterbi decoding is done in DEC1 and feed to

the mapper), a detector to compare the first symbol to the quantized first symbol, and

an oscillator having a tunable output as a function of the comparison (figure 2, figure 3

and page 5/1 section II.A the VCO in inherited in the PLL); and a turbo decoder coupled

to the receiver and adapted to accept an output of the receiver as input (figure 2 modulo

of turbo-decoder pages 5/1-5/2 section II.A), where the quantizing of the first symbol by

the Viterbi decoder of the receiver is independent of the turbo decoder (page 5/1 last

paragraph "A tentative decision is extracted from the turbo decoder during the decoding

process, and not after the complete decoding. Although the reliability of the decision

improves along with the iterative process, we cannot use a decision with an excessive

delay in order to guarantee the stability of the phase-locked loop (PLL); thus since the

delay introduced by the interleaver is too long, the extraction of the TD is performed

before the first interleaver", so the Viterbi decoder is independent of the turbo decoding

because it is perform before the turbo decoding and doesn't use the output of the turbo

decoder, in fact the first Viterbi decoder will only take into account the first encoder, and it is performed before the deinterleaver, so the turbo decoding process is not taken into account). The specification doesn't disclose what "independent" means, so the Examiner has used what he thinks is the best definition that applies to this case. The Viterbi decoder is independent of the turbo decoding because it is perform before the turbo decoding and doesn't use the output of the turbo decoder, in fact the Viterbi decoder is performed before the deinterleaver and only take into account the first encoder without considering the interleraving/deinterleaving process inherently in the turbo coding/decoding, and it, that means that the turbo decoding process is not taken into account, so it is independent of the turbo decoding.

As per claim 54 Langlais et al. teach that the transmitter modulates the first and second symbols on a carrier frequency, and the receiver further comprises a multiplier to multiply each of the first and second symbols with the oscillator output to recover its respective symbol by removing its respective carrier frequency (page 5/1 section I, figure 2 multiplier, figure 3 and page 5/1 section II.A the VCO in inherited in the PLL).

As per claim 56 Langlais et al. teach that the detector comprises a phase detector to detect a phase difference between the first symbol and the quantized first symbol (figure 2 phase detector page 5/1 section II.A).

As per claim 57 Langlais et al. teach that the oscillator comprises a voltage controlled oscillator (figure 2, figure 3 and page 5/1 section II.A the VCO in inherited in the PLL).

As per claim 58 Langlais et al. teach that the transmitter further comprises a

turbo encoder to turbo encode the signals before transmission to the receiver (page 5/1

section I).

As per claim 59 Langlais et al. teach that the turbo encoder comprises a trellis

encoder to encode a first portion of the signals including the fist and second symbols,

and an interleaver coupled to a trellis encoder to process a second portion of the signal

(page 5/2 section II.A last paragraph inherit to the turbo trellis in the receiver will be the

trellis in the transmitter and the interleaver).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

Claims 9, 13-14, 38-39 and 46 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Langlais et al. ("Synchronization in the carrier recovery of a satellite

link using turbo-codes with the help of tentative decisions", IEE Colloquium on Turbo

Codes in Digital Broadcasting - Could It Double Capacity? 22 Nov. 1999 pages: 5/1 -

5/7) as applied to claims 1, 11, 15, 35, and 33 above, and further in view of Divsalar (US

6023783 A).

Langlais teach claims 1, 11, 33 and 35. Langlais discloses a turbo encoder

comprised with two trellis encoders separated by an interleaver. Langlais doesn't

disclose two (or more) trellis encoders separated by interleavers may be used. Divsalar

discloses two (or more) trellis encoders separated by interleavers may be used (figure 2

column 5 line 37 column 12 line 14). Langlais and Divsalar teachings are analogous art

because they are from the same field of endeavor. At the time of the invention it would

have been obvious to a person of ordinary skill in the art to integrate the multiple

encoders disclosed by Divsalar with the carrier recovery scheme taught by Langlais.

The suggestion/motivation for doing so would have been to improve the performance of

the decoder (Divsalar abstract). Therefore, it would have been obvious to combine

Langlais and Divsalar to obtain the invention as specified in claims 9, 13-14, 38-39 and

46.

Claims 12, 20, 26, 32, 37,52 and 59-61 are rejected under 35 U.S.C. 103(a) as

being unpatentable over Langlais et al. ("Synchronization in the carrier recovery of a

satellite link using turbo-codes with the help of tentative decisions", IEE Colloquium on

Turbo Codes in Digital Broadcasting - Could It Double Capacity? 22 Nov. 1999 pages:

5/1 - 5/7) as applied to claim 11 above, and further in view of Robertson et al.,

"Bandwidth-Efficient Turbo Trellis-coded Modulation Using Punctured Component

Codes," IEEE Journal on Selected Areas in Communications; 02/1998,.p.p. 206-218,.

Vol. 16, No. 2).

As per claims 12, 37 and 61 Langlais teach claims 11, 36 and 58. Langlais

doesn't specifically teach that the signals comprise interleaving and de-interleaving of

the turbo encoded signals before transmission. Robertson teaches that the turbo-coded

transmitted signals comprise interleaving and de-interleaving of the turbo encoded

signals before transmission (figure 2 and 2 page 208 section II the encoder). Langlais

and Roberson teachings are analogous art because they are from the same field of endeavor. At the time of the invention it would have been obvious to a person of ordinary skill in the art to integrate the interleaving and de-interleaving of the turbo encoded signals before transmission taught by Roberson with the carrier recovery scheme taught by Langlais. The suggestion/motivation for doing so would have been to ensure that the ordering of the two information bits partly defining each symbol corresponds to that of the first encoder (Roberson page 208 section II. A) and to reduce the latency of the turbo decoder. Therefore, it would have been obvious to combine Langlais and Roberson to obtain the invention as specified in claims 12, 37 and 61.

As per claims 20, 26, 32 and 52 Langlais et al. teach claims 15, 21, 27 and 47. Langlais doesn't teach a switch between the multiplier and the Viterbi decoder input. Robertson teaches a switch between the multiplier and the decoder input (figures 4 and 5 pages 211, 212 and 213 section III the decoder). Langlais and Roberson teachings are analogous art because they are from the same field of endeavor. At the time of the invention it would have been obvious to a person of ordinary skill in the art to incorporate the switch between the multiplier and the decoder input taught by Roberson with the carrier recovery scheme taught by Langlais. The suggestion/motivation for doing so would have been to ensure that the ordering of the two information bits partly defining each symbol corresponds to that of the encoder (Roberson page 208 section II. A) and to reduce the latency of the turbo decoder. Therefore, it would have been obvious to combine Langlais and Roberson to obtain the invention as specified in claims 20, 26, 32 and 52.

As per claim 59 Langlais et al. teach claim 58. Langlais doesn't specifically indicate the turbo encoder comprising a trellis encoder to encode a first portion of the signals including the fist and second symbols, and an interleaver coupled to a trellis encoder to process a second portion of the signal. Robertson specifically teaches (title: "...turbo trellis-coded...") a turbo encoder comprising a trellis encoder to encode a first portion of the signals including the fist and second symbols, and an interleaver coupled to a trellis encoder to process a second portion of the signal (figures 1 and 2 page 207 section II the encoder). Langlais and Roberson teachings are analogous art because they are from the same field of endeavor. At the time of the invention it would have been obvious to a person of ordinary skill in the art to supplement the turbo trellis code and the interleaving turbo-trellis encoded signals taught by Roberson with the carrier recovery scheme taught by Langlais. The suggestion/motivation for doing so would have been to obtain a more powerful bandwidth-efficient encoder (Roberson page 206 abstract). Therefore, it would have been obvious to combine Langlais and Roberson to obtain the invention as specified in claim 59.

As per claim 60 Roberson and Langlais teach claim 59. Roberson also teaches that the receiver further comprises a switch positioned before the Viterbi decoder to pass only the first portion of the signal to the Viterbi decoder (introduction and figures 4 and 5 pages 211, 212 and 213 section III the decoder). Langlais and Roberson teachings are analogous art because they are from the same field of endeavor. At the time of the invention it would have been obvious to a person of ordinary skill in the art to

incorporate the switch between the multiplier and the decoder input taught by Roberson with the carrier recovery scheme taught by Langlais. The suggestion/motivation for doing so would have been to ensure that the ordering of the two information bits partly defining each symbol corresponds to that of the encoder (Roberson page 208 section II. A) and to reduce the latency of the turbo decoder. Therefore, it would have been obvious to combine Langlais and Roberson to obtain the invention as specified in claim 60.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Juan A. Torres whose telephone number is (571) 272-3119. The examiner can normally be reached on Monday-Friday 9:00 AM - 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mohammad H. Ghayour can be reached on (571) 272-3021. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free).

Juan Alberto Torres   KEVIN BURD
09-12-2005   PRIMARY EXAMINER